
## PANTEX ENVIRONMENTAL RESTORATION



## Perched Groundwater Pump and Treat Systems

he Pantex Groundwater Resource Conservation and Recovery Act Facility Investigation Report identified impacts to perched groundwater that require corrective action. The Pantex Site Wide Human Health Risk Assessment found that perched groundwater underneath the Pantex Plant contains high explosives and other constituents that could migrate over time to the Ogallala Aquifer, the main drinking water source for the area. The area of primary concern is in the southeast corner of the main Plant and offsite, adjacent to this area. The fine-grained zone prevents vertical migration in most areas, but becomes thinner and more permeable in the southeast where migration to the Ogallala Aquifer is possible.



Groundwater Beneath Pantex


Through extensive studies using groundwater fate and transport models, Pantex recognized that recharge occurring through Playa 1 created a subsurface mounding condition, which pushes high explosives and other chemicals in the perched groundwater to the southeast. Additionally, the slope of the confining layer (fine-grained zone) the perched aquifer sits upon allows the water to move downgradient toward the southeast.

As part of the corrective action identified in the Record of Decision and the Hazardous Waste Permit, Pantex operates two pump and treat systems, with 76 operating extraction wells and 4 injection wells that are capable of treating at least 550 gallons per minute (gpm) of contaminated perched groundwater. The pump and treat systems were installed to address contamination in areas where there is generally greater than 15 ft of saturation in the perched aquifer. These systems are designed to remove and treat groundwater to achieve contaminant mass reduction and reduction in the saturated thickness of the perched aquifer. Reduction in saturated thickness will significantly reduce the migration of contaminants both vertically and horizontally to prevent migration to the Ogallala Aquifer and so that natural breakdown processes can occur over time.

To achieve mass reduction and reduction in saturated thickness, the pump and treat systems treat the extracted water to levels safe for

residential use before the effluent is sent to wastewater treatment facility and irrigation system for beneficial use. The treated water is also used for industrial purposes including dust suppression, maintenance of landfill covers, and for industrial or construction operations as needed. Pantex also uses the treated water to mix with the amendment injected into the in situ bioremediation systems.

The Playa 1 Pump and Treat System (P1PTS) was installed by late 2008, and the system became fully operational in January 2009. This system was installed as part of the final Remedial Action to reduce the mound of water beneath Playa 1 that provides the driving force for water and contaminant movement to the southeast. The system also removes contaminant mass from the water before sending the treated water to be used beneficially, if available.



Plume Boundary and Groundwater Remedies (2021)

The Southeast Pump and Treat System (SEPTS) has been operating since 1995 when it started as a treatability study. It has been expanded with more

extraction wells and the capacity to treat boron and hexavalent chromium to become part of the final remedy for the southeastern portion of the groundwater plumes. The purpose of this system is to remove water and contaminant mass. While the primary goal is to beneficially use the water, the SEPTS retains the capability for injection back into the perched zone, as necessary. The pump and treat systems remove high explosives, primarily RDX, solvents such as TCE, hexavalent chromium, perchlorate and boron. The systems treat the water through a series of granular activated carbon tanks to remove organic contaminants including high explosives and solvents. Metals such as hexavalent chromium. perchlorate and boron are removed through ion exchange resin beds.




Ion Exchange and Effluent Tanks at SEPTS


The systems have treated an average of 230 million gallons of water and removed an average of 1,000 lbs of contaminants per year since the start of the Remedial Action. By 2021, Pantex treated 3.0 billion gallons of impacted perched water while removing about 16,050 lbs of contaminants.

Pantex has beneficially used about 65% of the treated water since the start of the Remedial Action. In areas under the influence of the pump and treat systems, water levels have declined at a rate of about 1 foot per year in most wells. Higher rates of decline have been observed in some areas.

It is expected to take several years of extracting water to fully affect the perched groundwater gradients in the southeastern area of the plume, thereby reducing movement of high explosives and other chemicals to the southeast. This action is one of several positive steps Pantex is taking to protect the Ogallala Aquifer.



SEPTS and P1PTS Wellfield



This document has been authored by Consolidated Nuclear Security, LLC, under Contract DE-NA-0001942 with the U.S. Department of Energy/National Nuclear Security Administration, or a subcontractor thereof. The United States Government retains and the publisher, by accepting the document for publication, acknowledges that the United States Government retains a nonexclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this document, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, or allow others to do so, for United States Government purposes.

## DISCLAIMER

This work of authorship and those incorporated herein were prepared by Consolidated Nuclear Security, LLC (CNS) as accounts of work sponsored by an agency of the United States Government under Contract DE-NA-0001942. Neither the United States Government nor any agency thereof, nor CNS, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility to any non-governmental recipient hereof for the accuracy, completeness, use made, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency or contractor thereof, or by CNS. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency or contractor (other than the authors) thereof.